IQL2 64 Thin Client

Entry-Level Dual Core Thin Client

VXL technology

4K DISPLAY Support

Front View

Rear View

The ultra-compact and lightweight, IQL2 series is a flexible and entry-level thin client designed to support excellent multimedia capabilities. Incorporating a superior build quality, the IQL2 series advanced features includes 4K dual displays, four USB3.0 ports and a powerful Intel® Apollo Lake Celeron™ N3350 Dual core System-on-a Chip (SoC), with a DDR3 memory controller.

An environmentally-friendly device, the IQL2 series efficient external power supply combined with a fan-less design, ensures a low power consumption and virtually silent operation.

Featuring an impressive three-year warranty backed by a comprehensive worldwide support network, the IQL2 series also includes a VESA mounting bracket and supports Fusion Universal Device Manager (UDM) Professional software which comes as standard.

The IQL2 series represents an unbeatable combination of affordability, quality, performance and service.

Key Features

- Gio6 Linux

- Intel® Apollo Lake Celeron™ N3350 Dual core SoC for a rich multimedia and graphics experience

- Built-in Intel HD 500 Series Graphics

- RAM: DDR3L 1600 MHz through 2 x SO-DIMM slot

- Flash: Onboard 32GB eMMC

- Built-in WiFi+Bluetooth (Optional)[1]

- Built-in Gigabit Ethernet networking with full duplex capability

- Dual digital display output (mDP and HDMI) with 4K resolution support.

- Fusion Universal Device Manager Professional included

- Kensington Lock

- VESA mounting bracket included

IQL2 64 Thin Client
Entry-Level Dual Core Thin Client

VXL technology

Technical specification

Operating System
• Gio6 Linux

Processor
• Intel® Apollo Lake Celeron™ N3350 upto 2.4 GHz Dual Core SoC
• 2MB shared L2 Cache
• Built-in Intel HD 500 Series Graphics Processor

System Memory
• RAM : 2 GB   upgradable upto 8 GB (with two SODIMM Slot)
• Flash: 8GB / 32 GB   (Flash with higher capacities are available through M.2 slot)
•

Display Support
• Dual digital display outputs with automatic setting of resolution and refresh rate
• Display Resolution (Max):
      mDP: 4096 x 2160 @60Hz (4K resolutions)
      HDMI: 3840 x 2160 @30Hz (4K resolutions)

Rear Panel
• 1 x DC in connector
• 2 x Gigabit RJ45 Port
• 1 x HDMI Port
• 1 x mDP Port

Front Panel
• Power Button
• 3 x USB 3.1 Gen1 Ports
• 1x USB 3.0 Type-C Port
• 1 x Combo Audio (Line out and MIC)

Optional
• Intel Dual Band Wireless-AC 3165 Wi-Fi/Bluetooth 4.2 combo adapter [1]
• HDMI to DVI-D Cable
• HDMI to VGA Dongle

External Power Adapter
• Wordwide auto-sensing 100-240 V AC
• DC output 19V / 3.42A

Networking
• Auto-sensing 10/100/1000 Mbps Gigabit LAN
• Wake On LAN

Operating Environment
• Operating Temperature: 0 to 40˚C
• Storage Temperature: −20 to 60˚C
• Humidity: 20% to 80% maximum,non-condensing

Included Accessories
• VESA Dock (100x100 or 75x75 mounting holes)

Physical Characteristics
• Dimension (W x D x H): 117x128x33 mm
• Weight : 0.45 kg

Regulatory Compliance
Safety and EMC:
• CE, FCC and BIS

Energy and Environment:
• RoHS

Warranty
• Three years limited warranty

Software Support
• Citrix Receiver
• VMware Horizon Client
• RDP
• XfreeRDP
• Firefox (ESR)
• X11/XDMCP
• REXEC
• Spice
• VNC
• SSH
• Text Editor
• Data Card
• File Manager
• Google-Chrome

Server OS Compatibility/Support
• Microsoft Windows Terminal Server Edition, Windows Server 2003/2008/2012
• Citrix XenApp / Citrix Presentation Server/ Citrix XenDesktop
• Protocol Support: TCP/IP, DHCP, FTP, HTTP, HTTPS

Setup and Configuration
• Boot from local flash
• Gio6 User interface language: US English
• Keyboard Language support: English, Spanish, French and German
• Scanners & Camera support
• Smartcard support
• ELO Touch screen support
• USB input devices support

Remote Management Tools
• Fusion Universal Device Manager (UDM) Professional
• Remote shadowing
• Reporting

Note:
  [1] Available for selected countries only

Part Numbers

Model No: IQL2 64 - F11R7 ----32GB Flash / 2 GB RAM
Model No: IQL2 64 - F11R8 ---- 32GB Flash / 4 GB RAM
Model No: IQL2 64 - F9R7   ----   8 GB Flash / 2 GB RAM

Contact Us

Americas
Woodlands Business Centre , 32315 Tamina Road, Suite A, Magnolia, TX 77354, USA
Tel: +1 877 242 7801

Europe
Carrington Business Park, Manchester Road, Manchester, M31 4DD, UK
Tel: +44 (0) 161 775 4755
France Tel . : +33 616624515
Germany Tel . : +49 (0) 8761 1093

United Arab Emirates
1610, Tiffany Tower, Cluster 'W', Jumeirah Lake Towers, Dubai, UAE
PO Box : 337111   Tel: +971 4 4508361

India
4th Floor, Kimatrai Building, 77/79, Maharshi Karve Marg, Marine Lines(E), Mumbai - 400002, India
Tel: +91 (0) 22 42203100

Asia Pacific
6167, Jalan Bukit Merah, Tower 4; #06-12 (SR-46), Singapore 150167
Tel: +65 6278 8180

E & OE: Specifications subject to change without notice. All trademarks are acknowledged and remain the property of their respective owners.

Document Version: A02